

Water Wash Control Panel

Hot Water Wash

MP10H

Manual Control, Single Sequence Wash for up to 50-ft (15 m) of water wash hood

General Description

Each water wash hood or group of hoods requires a control panel. The single sequence water wash control panel Model MP10H is for type “HD”, “HF” and “HT” type water wash hoods.

These control panels contain the electrical and plumbing required to automatically operate the exhaust fan and wash cycle. The model MP10H is a manual control with an ON/OFF selector switch. The single sequence wash can wash up to 50 feet (15m) of water wash hood.


Each time the exhaust fan is shut off manually, the groups of hoods connected to the control panel are

washed. At the end of the wash cycle the panel remains idle until the next ON and OFF sequence. Refer to the Spring Air Systems Hood Engineering Manual for detailed description of the control panel sequence of operation.


Hoods with HF or HT Fire Dampers

In the event that HF or HT UL/ULC listed fire damper assembly activates the fire damper closes, the exhaust and supply fans shut off, and both hot water wash solenoids turn on to flood the interior of the wash extractor with water.

Water Wash Panel Electrical Schematic



Water Wash Panel Plumbing



Engineering Data

Length of Hood per Wash Sequence		Control Panel Hot Water Connections	
ft	m	in	mm
Up to 10	Up to 3	0.75	19
Up to 20	Up to 6	1.00	25
Up to 35	Up to 10.5	1.25	32
Up to 50	Up to 15	1.50	3

Notes:

- All control panels are 30" x 33" x 7" (840 mm x 914 mm x 203 mm)
- The DB hood has an equivalent length of 1.5 the actual length of purposes of using this chart.

Installation

- The total length of hood connected to the control panel determines the sizes of the inlet and outlet pipe connections. Refer to the Engineering Data Chart to the left for Pipe size Vs Hood length.
- The remote piping must meet all local plumbing codes. The control panel must be installed with protection to stop the flow of detergent back into the potable water supply. Spring Air Systems will always prepipe the detergent line inside the water wash, plumbing enclosure panel unless advised otherwise prior to shipment.

Spring Air Systems Model No. MP10H Wash Panel Specification

The water wash control panel shall be a Spring Air Systems model no. MP10H manual, single wash sequence, UL/ULC listed, and CSA certified.

The panel shall include an integral micro-processor. The stainless steel water wash control panel shall contain all the electrical and plumbing components to operate the exhaust fan, and water wash cycle.

The electrical section shall include a ten-minute adjustable timer, an off/auto/on fan selector switch, and a wash on pilot light. The plumbing section shall include a hot water solenoid valve, hot water shut off valve, hot water line strainer, pressure/temp gauge, detergent pump, detergent check valve, and one litre of detergent.

The panel shall be either wall mounted or recessed where shown ready for interconnection of the mechanical and electrical services by the mechanical and electrical divisions as per the manufacturer instructions.

Engineering Data

Item Number	_____
Model Number:	MP10H-_____
Panel Dimensions	30" X 33" X 7"
Hot Water Inlet:	_____
Hot Water Outlet	_____
No. of Sequences:	One
Total Hot Water Flow @ 40 PSIG	_____ USGPM
Electrical:	120v/1/60 - 10 AMPS.